

Electric Battery Specifications

Model	Terminal Type	Voltage	Capacity Ah/20hours	Battery Dimension (mm)			
				L	W	H	TH
EB25LL	L	12	30	195	127	200	227
EB25T	T	12	30	195	127	200	222
EB35LL	L	12	42	236	127	200	227
EB35T	T	12	42	236	127	200	222
EB50LL	L	12	60	256	170	201	228
EB50LR	L	12	60	256	170	201	228
EB50T	T	12	60	256	170	201	224
EB50V	V	12	60	256	170	201	250
EB65LL	L	12	80	303	170	201	228
EB65LR	L	12	80	303	170	201	228
EB65T	T	12	80	303	170	201	224
EB65V	V	12	80	303	170	201	250
EB90T	T	12	110	406	173	209	232
EB100LL	L	12	120	406	173	209	241
EB100LR	L	12	120	406	173	209	241
EB100T	T	12	120	406	173	209	232
EB100V	V	12	120	406	173	209	256
EB130LL	L	12	160	502	180	210	255
EB130LR	L	12	160	502	180	210	255
EB130T	T	12	160	502	180	210	255
EB160LL	L	12	190	505	220	210	255
EB160LR	L	12	190	505	220	210	255
EB160T	T	12	190	505	220	210	255
EBB100V	V	12	100	406	170	213	262
EBB125LL	L	12	125	406	170	213	245
EBB125V	V	12	125	406	170	213	262
EBZ60T	T	12	60	256	170	201	224
EBZ80T	T	12	80	303	170	201	224
EBZ110T	T	12	110	406	173	209	232
EBZ130V	V	12	125	406	170	213	262
EBZ160T	T	12	160	502	180	210	255
EBZ200T	T	12	200	505	220	210	255

Technical Information

