

Sealed Maintenance Free (JIS)

08

For Japanese Vehicles

Model	Capacity at 20hr (AH)	Plate/Cell (PCS)	Battery Dimensions (mm)				CCA (IEC)	RC (MIN)	Cell Layout
			L	W	H	TH			
44B19R	38	10	187	127	199,5	222	330	52	1
44B19L	38	10	187	127	199,5	222	330	52	0
60B24R	48	12	236	129	200	222	400	75	1
60B24L	48	12	236	129	200	222	400	75	0
48D26R	50	10	257	173	203	222	400	85	1
48D26L	50	10	257	173	203	222	400	85	0
55D26R	60	12	257	173	203	222	550	100	1
55D26L	60	12	257	173	203	222	550	100	0
75D26R	65	12	257	173	203	222	550	100	1
75D26L	65	12	257	173	203	222	550	100	0
80D26R	70	13	257	173	203	222	580	120	1
80D26L	70	13	257	173	203	222	580	120	0
65D31R	70	14	303	173	203	222	600	130	1
65D31L	70	14	303	173	203	222	600	130	0
75D31R	75	14	303	173	203	222	600	130	1
75D31L	75	14	303	173	203	222	600	130	0
95D31R	80	15	303	173	203	222	660	140	1
95D31L	80	15	303	173	203	222	600	140	0
105D31R	85	16	303	173	203	222	670	140	1
105D31L	85	16	303	173	203	222	670	140	0
110D31R	95	18	303	173	203	222	750	155	1
110D31L	95	18	303	173	203	222	750	155	0